

ECONOMY PURE STOCK CLASS RULES

- Stock type flat top 4 eyebrow cast piston and or stock replacement 4 eyebrow forged pistons.
- Carburetors are quadrajet or 1850 Holleys that are unaltered with a single gas feed.
- Zero deck allowed.
- Stock rods and stock crank shaft only. (No aftermarket)
- Open chamber heads only, 70 ccs. No vortex or aftermarket heads.
- Stock push rods only.
- No port or polishing at all on heads or blocks.
- 3/8 studs in head's can be screw in or pinned.
- Stock rocker 1:5 stock rocker nuts and rocker arm balls.
- 1.50 – 1.94 Valve size. No oversized valves.
- Must be hydraulic CAM only, maximum 425/425. Can use anti-pump up lifters.
- The front engine pulleys can be after market.
- The steering pump can be after market.
- The water pump can be after market.
- Cast iron Intake 4-barrel must be stock GM.
- No bow tie intakes allowed.
- No aftermarket intakes allowed.
- Distributors HEI only. May be locked.
- NO MSD.
- Plug wires may be aftermarket.

ENGINE PROTESTS RULES:

- Protests are only for complete engine only.
- \$500 for a complete engine tear down (cash only).
- Costs are responsibility of protesting party.
- The Protest must occur within 15 minutes after the completion of the race.
- The winner of the race can only be protested by the second-place car.